FORM PTO		U S DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER
`		LETTER TO THE UNITED STATES	MERCK 2372
1		O/ELECTED OFFICE (DO/EO/US)	US APPLICATION NO (If known, see 37 CFR §1 5)
		G A FILING UNDER 35 U.S.C. §371	10/048157
INTERNA	FIONAL APPLICATION NO	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED
PCT/E	EP00/06317	5 JULY 2000	29 JULY 1999
TITLE OF	INVENTION		
NITRAT	TION IN A STATIC MIC	ROMIXER	
APPLICAN	VT(S) FOR DO/EO/US		
WUR	ZIGER, Hanns, et a	1.	
Applica	nt herewith submits to tl	ne United States Designated/Elected Office (DO/EO/US) the fe	ollowing items and other information:
I. 💻	This is a FIRST submis	sion of items concerning a filing under 35 U.S.C. §371	
2.		UBSEQUENT submission of items concerning a filing under 35	·
3.	This express request to be expiration of the application	begin national examination procedures (35 U.S.C. §371(f)) at any ble time limit set in 35 U.S.C. §371(b) and PCT Articles 22 and	time rather than delay examination until the 39(1).
4.	A proper Demand for In	ternational Preliminary Examination was made by the 19th month	from the earliest claimed priority date.
5.	A copy of the Internatio	nal Application as filed (35 U.S.C. §371(c)(2))	
	a. is transmitted	herewith (required only if not transmitted by the International Bu	reau).
	b. has been trans	mitted by the International Bureau.	
	c. is not required	, as the application was filed in the United States Receiving Office	ce (RO/US).
6.	A translation of the Inter	rnational Application into English (35 U.S.C. §371(c)(2)).	
7.	Amendments to the class	ns of the International Application under PCT Article 19 (35 U.S.	S.C. §371(c)(3))
	a are transmitted	I herewith (required only if not transmitted by the International B	ureau).
		smitted by the International Bureau.	
	_	made; however, the time limit for making such amendments has	NOT expired
	d. have not been	made and will not be made.	
8.	A translation of the ame	ndments to the claims under PCT Article 19 (35 U S.C. §371(c)(	3)).
9. 🗆	An oath or declaration o	f the inventor(s) (35 U.S.C §371(c)(4))	
10.		exes to the International Preliminary Examination Report under P	CT Article 36 (35 U.S.C. §371(c)(5)).
11. 🗆		ocument(s) or information included:	;
12.		ire Statement under 37 C.F.R §§1.97 and 1.98.	DD 000 00 1001
	<del>-</del>	t for recording. A separate cover sheet in compliance with 37 C.	F.R. §§3 28 and 3.31 is included
13.	A FIRST preliminary an		
		QUENT preliminary amendment.	
14.	A substitute specification		
15.		torney and/or address letter.	}
16.	Other items or informati	on·	
			i

U.S. APPLICATION NO (1f km	lown_see 37 CFR §1 5)	INTERNATIONAL APPLICATION NO		ATTORNEY'S DOCKET NUM	<b>MBER</b>
U.S. APPLICATION NO (1f km	U4815F	PCT/EP00/06317		MERCK 2372	
17. A The following	g fees are submitted:			CALCULATIONS	PTO USE ONLY
	IONAL FEE ( 37 CFR §1.4	492 (a) (1) - (5)):			
Search Repor	t has been prepared by the E	PO or JPO	\$890.00		
International	preliminary examination fee	paid to USPTO (37 CFR §1.482	2) \$710.00		
No internetio	nal preliminary evamination	fee paid to USPTO (37 CFR §1. O (37 CFR §1.445(a)(2))	.482)		
international	search fee (37 CFR §1.445(a	tion fee (37 CFR §1.482) nor a)(2)) paid to USPTO			
International and all claims	s satisfied provisions of PCT	paid to USPTO (37 CFR §1.482 Article 33(2)-(4)	\$100.00	<b>***</b>	
	ENTER APP	ROPRIATE BASIC FE	EE AMOUNT =	\$890.00	
Surcharge of \$130.00 for months from the earlies	or furnishing the oath or dec st claimed priority date (37 C	laration later than C.F.R. §1.492(e)).	30		
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	9 - 20 =	0	x \$ 18.00	\$0.00	
Independent claims	1 - 3 =	0	x \$ 84.00	\$0.00	
MULTIPLE DEPEND	ENT CLAIM(S) (if applicab		+ \$ 280.00		
	TO	TAL OF ABOVE CAL	CULATIONS =	\$890.00	
Reduction of 1/2 for fil	ing by small entity, if applic	able. A Verified Small Entity St	tatement must also be		
			SUBTOTAL =	\$890.00	
Processing fee of \$130 months from the earlies	.00 for furnishing the Englis st claimed priority date (37 C	h translation later than 20 C.F.R. §1 492(f)).	□ 30		
		TOTAL NA	TIONAL FEE =	\$890.00	
Fee for recording the e	nclosed assignment (37 C.F. neet (37 C.F.R. §§3.28, 3.31)	R. §1.21(h)). The assignment m	ust be accompanied by	у	
an appropriate cover si			S ENCLOSED =	\$890.00	
				Amount to be refunded.	
				charged:	
a. A check in	the amount of \$890.0	to cover the above fees i	s enclosed		
A duplica	arge my Deposit Account te copy of this sheet is enclo	osed.		to cover the above fees	
		d to charge any additional fees v duplicate copy of this sheet is e		, or credit any overpayme	ent to
NOTE: Wher	re an appropriate time T.R. §1.137(a) or (b)) m	limit under 37 C.F.R. §§1. ust be filed and granted to	494 or 1.495 has n restore the applic	ot been met, a petiti ation to pending sta	on to tus.
	NDENCE TO: Customer Num				
		:	aran h		
ĺ·	23599		SIGNATURE	- //	
	PATENT TRADEMARK OFFICE		Anthony .  NAME	J. ZGIANO	
Filed: 29 JANU	IARY 2002	/	27,969		
AJZ:kmo	/MT 2002			ION NUMBER	
1 13 Z.Killo					

Tuders Tala Linate Library

# JC13 Rec'd PCT/PTO 29 JAN 2002

#### APPLICATION DATA SHEET

#### APPLICATION INFORMATION

Application Type:: Subject Matter::

CD-ROM or CD-R?::

Title::

Attorney Docket Number::

REGULAR

UTILITY

NONE

NITRATION IN A STATIC MICROMIXER

**MERCK 2372** 

#### INVENTOR INFORMATION

Applicant Authority Type:: Primary Citizenship Country::

Status::

Given Name::

Family Name::

City of Residence::
Country of Residence::

Street of Mailing Address::

City of Mailing Address::
Country of Mailing Address::

Postal or Zip Code of Mailing Address::

Applicant Authority Type:: Primary Citizenship Country::

Status::

Status::
Given Name::

Family Name:: City of Residence::

Country of Residence::

Street of Mailing Address::

City of Mailing Address::
Country of Mailing Address::

Postal or Zip Code of Mailing Address::

Applicant Authority Type:: Primary Citizenship Country::

Status::

Given Name:: Family Name::

INVENTOR

Germany

FULL CAPACITY

Hanns

WURZIGER Darmstadt

Germany

Greinstrasse 7b

Darmstadt

Germany D-64291

INVENTOR

Germany

FULL CAPACITY
Joeran

STOLDT

Weiterstadt Germany

Kreuzstrasse 11

Darmstadt

Germany D-64331

INVENTOR

Germany

FULL CAPACITY

Kai

**FABIAN** 

City of Residence::

Wilhelmsfeld

Country of Residence::

Germany

Street of Mailing Address::

Oberer Langeraim 13

City of Mailing Address::

Wilhelmsfeld

Country of Mailing Address::

Germany

Postal or Zip Code of Mailing Address::

D-69259

**Applicant Authority Type::** 

INVENTOR

Primary Citizenship Country::

Germany

Status::

FULL CAPACITY

Given Name::

Norbert

Family Name::

SCHWESINGER

City of Residence::

Ilmenau

Country of Residence::

Germany

Street of Mailing Address::

Sturmheide 10

City of Mailing Address::

Ilmenau

Country of Mailing Address::

Postal or Zip Code of Mailing Address::

Germany D-986936

**CORRESPONDENCE INFORMATION** 

Correspondence Customer Number::

23599

REPRESENTATIVE INFORMATION

Representative Customer Number::

23599

## DOMESTIC PRIORITY INFORMATION

Application::	Continuity Type::	Parent Application::	Parent Filing Date::
This Application	National Stage of	PCT/EP00/06317	07/05/00

## FOREIGN PRIORITY INFORMATION

<b>Application Number:</b>	Country::	Filing Date::	Priority Claimed::
199 35 692.0	Germany	07/29/99	YES

#### ASSIGNMENT INFORMATION

Assignee Name::

Merck Patent GmbH

Street of Mailing Address::

Frankfurter Strasse 250

City of Mailing Address::

Darmstadt

Country of Mailing Address::

**GERMANY** 



Postal or Zip Code of Mailing Address:: 64293

JC13 Rec'd PCT/PTO 29 JAN 2002

## IN THE UNITED STATES DESIGNATED/ELECTED OFFICE

International Application No.

PCT/EP00/06317

International Filing Date

5 JULY 2000

Priority Date(s) Claimed

29 JULY 1999

Applicant(s) (DO/EO/US)

WURZIGER, Hanns, et al.

Title: NITRATION IN A STATIC MICROMIXER

#### PRELIMINARY AMENDMENT

Commissioner for Patents Washington, D.C. 20231

SIR:

ì

Prior to calculating the national fee, and prior to examination in the National Phase of the above-identified International application, please amend as follows:

#### IN THE CLAIMS:

- 3. (Amended) Process according to Claim 1, characterized in that the process is continuous.
- 4. (Amended) Process according to Claim 1, characterized in that
  - a) the aromatic or heteroaromatic compound is firstly derivatised,
  - b) the resultant derivative is dissolved in a solvent and
  - c) nitrated in a micromixer using a nitrating reagent, and
  - d) the nitrated product is isolated from the resultant solution.
- 5. (Amended) Process according to Claim 1, characterized in that the nitrated product is separated off from the reaction mixture by extraction with a solvent.

- 6. (Amended) Process according to Claim 1, characterized in that the reaction mixture flows through the microreactor at an adequate flow rate of from 1µl/min to 10ml/min, and the reaction is carried out at a temperature in the range from -40 to 150°C, with the course of the reaction being monitored by gas chromatography.
- 8. (Amended) Process according to Claim 4, characterized in that an aromatic or heteroaromatic compound is converted into a carbamate in a first reaction step.
- 9. (Amended) Process for the nitration of aromatic or heteroaromatic compounds selected from the group consisting of toluene, 1,2,3,4-tetrahydroisoquinoline, N-methoxycarbonyl-1,2,3,4-tetrahydroisoquinoline and benzofuran derivatives according Claim 1.

## **REMARKS**

The purpose of this Preliminary Amendment is to eliminate multiple dependent claims in order to avoid the additional fee. Applicants reserve the right to reintroduce claims to canceled combined subject matter.

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached pages are captioned "Version With Markings to Show Changes Made".

Respectfully submitted,

Anthony J. Zelano, Reg. No. 27,969

Attorney for Applicants

MILLEN, WHITE, ZELANO & BRANIGAN, P.C.

Arlington Courthouse Plaza 1

2200 Clarendon Boulevard, Suite 1400

Arlington, VA 22201

Direct Dial: 703-812-5311 Facsimile: 703-243-6410 Email: zelano@mwzb.com

AJZ:kmo

Filed: 29 January 2002

## VERSION WITH MARKINGS TO SHOW CHANGES MADE

Claims 3 to 6, 8 and 9 were amended as follows:

- 3. (Amended) Process according to Claims 1-and 2, characteriszed in that the process is continuous.
- 4. (Amended) Process according to Claims 1-to 3, characteriszed in that
  - a) the aromatic or heteroaromatic compound is firstly derivatised,
  - b) the resultant derivative is dissolved in a solvent and
  - c) nitrated in a micromixer using a nitrating reagent, and
  - d) the nitrated product is isolated from the resultant solution.
- 5. (Amended) Process according to one or more of Claims 1 to 4, characteriszed in that the nitrated product is separated off from the reaction mixture by extraction with a solvent.
- 6. (Amended) Process according to one or more of Claims 1-to-5, characteriszed in that the reaction mixture flows through the microreactor at an adequate flow rate of from 1µ1/min to 10m1/min, and the reaction is carried out at a temperature in the range from -40 to 150°C, with the course of the reaction being monitored by gas chromatography.
- 8. (Amended) Process according to Claims 4 to 7, characteriszed in that an aromatic or heteroaromatic compound is converted into a carbamate in a first reaction step.
- 9. (Amended) Process for the nitration of aromatic or heteroaromatic compounds selected from the group consisting of toluene, 1,2,3,4-tetrahydroisoquinoline, N-methoxycarbonyl-1,2,3,4-tetrahydroisoquinoline and benzofuran derivatives according to one or more of Claims 1 to 8.

10

15

20

25

30

35

2/prts -1-

10/048157 JC13 Rec'd PCT/PTO 29 JAN 2002

## Nitration in a static micromixer

The present invention relates to a novel process for the nitration of organic compounds, preferably of aromatic and heteroaromatic compounds, using nitrating reagents which are known from the literature and new types of nitrating reagents.

The nitration of organic substrates is a very important and frequently performed process in the chemical industry. Numerous publications relate to this subject.

Particular safety problems exist on performance of nitrations on an industrial scale, since firstly in some cases highly toxic chemical substances have to be used which, even considered alone, represent a considerable risk to the environment. Secondly, nitrations generally proceed in a highly exothermic manner, which means that there is an increased risk of explosion when carrying out these reactions.

There has hitherto been no lack of attempts to reduce these safety problems. However, as soon as large amounts of nitrated products are to be prepared and a scale-up is to be carried out, the above-mentioned safety problems come to the fore.

The object of the present invention was therefore to provide a novel process which is simple to carry out and an apparatus which enable nitrations of organic compounds, in particular of aromatic and heteroaromatic compounds, to be carried out in a simple, reproducible manner with increased safety, with reduced residual risk to the environment. A further object of the invention was to provide correspondingly nitrated products in increased yields and improved purities.

The object is achieved by a process for the nitration of aromatic or heteroaromatic compounds in which the aromatic or heteroaromatic compound in liquid form or in solution is mixed intensively and allowed to react with a liquid or dissolved nitrating reagent, selected from the group consisting of dilute nitric acid, 100% nitric acid, potassium nitrate in 100% sulfuric acid, mixtures of nitric acid and sulfuric acid ("nitrating acid"), nitric acid esters, mixtures of nitric acid with inorganic and organic anhydrides and dinitrogen pentoxide,

10

20

35

2001

in a microreactor for an adequate residence time, and the desired nitration product is isolated from the resultant reaction mixture.

The microreactor used when carrying out the process is preferably a heatable flow reactor.

The object is furthermore achieved by a process which can be carried out continuously.

A particular variant of the process according to the invention consists in that a) the aromatic or heteroaromatic compound is firstly derivatised,

- b) the resultant derivative is dissolved in a solvent and
- c) nitrated in a micromixer using a nitrating reagent, and
- d) the nitrated product is isolated from the resultant solution.
- The nitrated product is preferably separated off from the reaction mixture by extraction with a solvent, since this represents a simple form of work-up.
  - In accordance with the invention, the reaction mixture is pumped into the microreactor in such a way that it flows through the latter at a flow rate of at least 5 µl/min, and the reaction is carried out at a temperature in the range from -10 to 80°. At the same time, the course of the reaction is, if desired, monitored by gas chromatography. If desired, this can be carried out continuously.
- If desired, the process according to the invention is carried out after the aromatic or heteroaromatic compound has been converted into a carbamate in a first reaction step.
- In particular, the process according to the invention is used for the nitration of compounds selected from the group consisting of toluene, 1,2,3,4-tetrahydro-isoquinoline, N-methoxycarbonyl-1,2,3,4-tetrahydroisoquinoline and benzofuran derivatives.
  - Various publications and patent applications disclose miniaturised flow reactors for organic reactions. Reactors of this type are preferably produced from thin silicon structures bonded to one another. Miniaturised reactors of this type have very narrow channels which, per se, tend to block very easily due to particles present or formed in the reaction solution.

Save date: 30.11.01 12:17 Print date: 04 12 01 12:14 The prerequisites for the ability to carry out a reaction in miniaturised flow reactors of this type therefore consist in that it can be carried out in the homogeneous liquid phase, and precipitations or the formation of particles during the reaction can be prevented.

5

In order to achieve the present object, numerous attempts to nitrate organic compounds, in particular aromatic and heteroaromatic compounds, have been carried out.

10

8-Nitro-N-methoxycarbonyltetrahydroisoquinoline, for example, is required as intermediate for the synthesis of chemical compounds used as active ingredients for the preparation of medicaments. This compound can be prepared by methods known from the literature, to be precise by nitration of 1,2,3,4-tetrahydroisoquinoline using potassium nitrate in concentrated sulfuric acid followed by acylation in accordance with the general reaction equation given below:

15

$$\bigcap_{NH} \longrightarrow \bigcap_{N} \bigcap_{NH} \longrightarrow \bigcap_{N} \bigcap_{N$$

20

As part of the experimental programme mentioned above, it has been attempted to carry out this reaction with the aid of a microreactor. However, owing to the viscosity of 100% sulfuric acid, a considerable pressure built up in the micromixer and in the thin Teflon tubes. It has been found that this problem can be overcome with the aid of an injection pump operating at very low pump output.

25

Subsequent experiments showed very efficient nitration results. When the reaction was complete, a liquid reaction mixture was obtained which had to be neutralised before the desired products were separated off.

30

However, since the aim was to provide a process which can be carried out simply and in an environmentally friendly manner, alternatives were sought.

35

Surprisingly, it has been found that an altered sequence of the synthesis enables this problem to be circumvented.

In a first step, 1,2,3,4-tetrahydroisoquinoline is converted into the corresponding carbamate. The carbamate is dissolved in a suitable solvent, such as, for example, dichloromethane, and nitrated at ambient temperature using 65% nitric acid.

5

2001

Optimisation experiments have shown that this nitration can be carried out at a flow rate of 5 µl/min in the microreactor with a good result, based on the ratio of starting compounds employed to product obtained. The nitration product obtained in this way can advantageously be isolated directly from the acidic reaction solution by extraction.

15

10

20

The process thus found for carrying out the desired reaction in a microreactor through which flow takes place is superior to a reaction in the stirred reactor usually used.

25

A very particular advantage is that, as soon as the performance parameters, such as temperature and flow rate, have been set and the system is in equilibrium, the reaction can be carried out continuously as long as there is a need for the desired reaction product. In addition, the product can be obtained in constant quality with stable yields. Correspondingly impressive results have been achieved, for example, in the nitration of N-methoxy-carbonyl-1,2,3,4-tetrahydroisoquinoline in a continuous reaction, with the latter being maintained at equilibrium for the duration of six days.

30

The possibility of using the microreactor for further aromatic and heteroaromatic compounds has also been investigated. The nitration of toluene is described here in greater detail by way of example.

35

In a first series of experiments, toluene was mixed with an equivalent amount of dichloromethane and nitrated at various temperatures using 65% nitric acid. The ratio of the nitrated isomers to unreacted toluene is shown in the

10

2001

following table. The data are based on reactions at 10, 20 and 30°C. The isomer ratio was determined from HPLC analyses. However, the HPLC signals were not separated from one another sufficiently cleanly to allow the amount of meta-isomers formed to be determined precisely. However, it can be concluded from the results obtained that the results achieved correspond to those from the literature.

Temperature [°C]	Ortho- nitrotoluene	Para- nitrotoluene	Toluene
0	41%	22%	37%
20	59%	40%	-
30	59%	41%	-
Literature <sup>2</sup>	59%	37%	

For comparison, toluene in undiluted form was nitrated at various tempera-15 tures using 100% nitric acid. The results are shown in Figure 1. It can be seen therefrom that the proportion of the ortho-product drops with increasing temperature, while the formation of the para-substituted toluene and the meta-form formed in small amounts increases.

20 Provided that, during passage through the microsystems, all substances remain in the dissolved liquid phase and do not precipitate out, all nitrations can be carried out using the following nitrating reagents described in the literature:

- dilute nitric acid 25
  - 100% nitric acid
  - potassium nitrate in 100% sulfuric acid
- mixtures of nitric acid and sulfuric acid ("nitrating acid") 30
  - nitric acid esters, in general
  - mixtures of nitric acid with inorganic and organic anhydrides
- dinitrogen pentoxide 35

Save date: 30,11.01 12:17

The nitrations described proceed with good to very good yields in the static micromixer. The selectivity can be influenced by varying various parameters, such as, for example, concentration, temperature (see Figure 2) or residence time.

5

2001

The advantage of nitration in microfluid systems consists in better mass and heat transport, improved control of the reaction time and increased safety. The very small amounts of reagent present in the system are responsible for this.

10

This point is particularly important in the case of nitrations, which are generally highly exothermic, if, for example, the mixture consisting of 100% nitric acid and acetic anhydride, which reacts very selectively – the reactive species is the acetyl nitrate, which decomposes in an explosive manner at about 60°C – is employed.

15

A change in the residence time by variation of the pump output exhibited only a slight effect on the selectivity, or none at all, in this case. It can also be assumed that the activity of the nitrating reagents and the temperature have virtually no effect on the quantitative result of the reaction at a defined residence time.

20

This effect is significantly more pronounced if a mixture of toluene and acetic acid is treated with 100% nitric acid. In this case, the reacting reagent is acetyl nitrate, which is in some cases, depending on the species to be nitrated, regarded as a significantly more reactive, but also more selective nitrating reagent than nitric acid alone.

25

A mixture consisting of nitric acid and acetic anhydride or pre-distilled acetyl nitrate is a strong, but also hazardous reagent since it decomposes above 60°C.

30

By means of this reagent, it is even possible to nitrate heterocyclic compounds, which otherwise can only be nitrated with difficulty. For understandable reasons, however, this method normally only finds limited use.

In contrast to the situation in the industrial plants usually used for carrying out chemical reactions, firstly the temperature of the reaction mixture can be kept constant in each volume element in the micromixer systems according to the invention in accordance with the process according to the invention.

- Secondly, only very small amounts of starting material are present in the apparatus at any point in time. This means that the nitration reactions described, which were hitherto only possible using special and expensive safety precautions, can be carried out readily in the present micromixer system.
- The process according to the invention can be used in a simple manner for carrying out, for example, nitrations of toluene, 1,2,3,4-tetrahydroisoquinoline, N-methoxycarbonyl-1,2,3,4-tetrahydroisoquinoline and of benzofuran derivatives.
- Suitable aromatic compounds are furthermore all monocyclic and polycyclic, homoaromatic or heteroaromatic compounds, as well as compounds which have a monocyclic or polycyclic, homoaromatic or heteroaromatic basic structure or partial structure, for example in the form of substituents.
- Suitable aromatic compounds are, in particular: benzene and derivatives thereof, naphthalene and derivatives thereof, azulene and derivatives thereof, anthracene and derivatives thereof, phenanthrene and derivatives thereof,
- pyrene and derivatives thereof,
  fluorene and derivatives thereof,
  quinones, such as, for example, ortho- and para-benzoquinone, and
  derivatives thereof, all naphthoquinones known to the person skilled in the art
  and derivatives thereof, fluorenones, anthrones, phenanthrones, all known
  anthraquinones and derivatives thereof.
  - Heteroaromatic compounds which can be employed are the following:
- oxygen-containing heteroaromatic systems (furans), such as, for example,
  - benzo-fused furans and derivatives thereof,

dibenzofurans and derivatives thereof, dibenzodioxanes and derivatives thereof, pyrylium cations and derivatives thereof, benzopyranones and derivatives thereof,

nitrogen-containing heteroaromatic systems and derivatives thereof, such as, for example,

pyrroles, pyrazoles, imidazoles, triazoles, tetrazoles, pyridines, pyrazines,
pyrimidines, pyridinium salts, triazines, tetrazines, pyridine-N-oxide and
derivatives thereof
benzo-fused pyrroles (indoles, carbazoles, benzimidazoles and benzotriazoles) and derivatives thereof,
phenazine and derivatives thereof,
quinolines and isoquinolines,
chinnolines, quinazolines and quinoxalines,
phenanthrolines and derivatives thereof,
bipyridyls and higher homologues,
acridines, acridones and derivatives thereof,
pyrene and derivatives thereof,

suitable sulfur-containing heteroaromatic systems and derivatives thereof are, for example,

thiophenes and derivatives thereof, .

benzo-fused thiophenes (benzothiophenes and dibenzothiophenes) and derivatives thereof.

It is also possible to employ acenaphthylene, thiazoles, isothiazoles, biphenylenes, purines, benzothiadiazoles, oxazoles and isooxazoles in the process according to the invention.

Suitable solvents for these nitrations are the following:

- dilute and concentrated acids, such as, for example, sulfuric acid, nitric acid, acetic acid and trifluoroacetic acid

35

10

- acid anhydrides, such as, for example, acetic anhydride and trifluoroacetic anhydride
- mixtures of acids and salts, such as, for example, concentrated sulfuric acid and KNO<sub>3</sub>, and also any other combination
- halogenated hydrocarbons, such as, for example, chloroform, carbon tetrachloride, dichloromethane and tetrachloroethane
- esters, such as, for example, ethyl acetate
- ethers, such as, for example, tetrahydrofuran, diethyl ether and tert-butyl methyl ether
- mixtures of the said solvents of all types
- ionic solvents, such as, for example, 1-ethyl-3-methylimidazolium tetrachloroaluminate, n-butylpyridinium tetrachloroaluminate or 1-ethyl-3-methylimidazolium tetrafluoroborate.
- Suitable solvents for the work-up/extraction are all organic solvents, in particular:
  - ethers, such as, for example, diethyl ether, tert-butyl methyl ether, tetrahydrofuran, etc.
- halogenated hydrocarbons, such as, for example, chloroform, carbon
   tetrachloride, dichloromethane, tetrachloromethane and tetrachloroethene
  - alcohols, such as, for example, methanol, ethanol, 1- and 2-propanol
  - nitriles, such as, for example, acetonitrile
- ketones, such as, for example, acetone
  - esters, such as, for example, ethyl acetate.
- Suitable for carrying out the nitrations described are micromixers as described, for example, in WO 96/30113 A1. Also suitable, however, are static micromixers of simpler design which effect sufficiently intensive mixing of the liquids employed in simple crossing channels and in which an

10

20

25

adequate residence time of the reaction mixture for the reaction in the reactor is ensured.

Basic prerequisites for the suitability of microreactors in the nitration process according to the invention are furthermore:

- the possibility of uniform temperatures in each volume element of the reactor.
- leak-proof and reliable connection means for supply and discharge lines for liquids, but where appropriate also for further equipment for reaction monitoring or for analytical purposes,
- leak-proof connection of the individual parts or structures forming the microreactor, both internally and to the outside, so that the liquid-carrying channels are separate from one another and the liquid cannot escape to the outside,
- easy handling in the event of faults.

For better understanding and in order to illustrate the present invention, examples are given below which are within the scope of protection of the present invention, but are not suitable for restricting the invention to these examples. The term "within the scope of the present invention" is also taken to mean, as already stated above, nitrations carried out using static miniaturised flow reactors which are likewise known to the person skilled in the art, but where the flow reactors used can allow larger flow rates for the preparation of larger amounts of product in the same time unit, and further both uniform temperatures and homogeneous mixing are ensured in each volume element of the reactor.

## **Examples**

# Example 1

1 g of 1,2,3,4-tetrahydroisoquinoline was carefully dissolved in 5 ml of concentrated sulfuric acid. The nitric acid was prepared by dissolving 1 g of potassium nitrate in 5 ml of concentrated sulfuric acid. Two 2 ml disposable plastic syringes were filled with the two solutions and attached to a Harvard Apparatus pump 22. The disposable syringes themselves were connected to a static silicon mixer, which was in turn

10

20

25

2001

connected to a thin Teflon tube having a diameter of 0.25 mm and a length of 80 cm. The reaction was carried out at ambient temperature at a flow rate of 5 µl/min. The reaction mixture formed was collected in a vessel filled with ice pieces and neutralised using 2N NaOH before the product formed was extracted with dichloromethane.

1 g of 1,2,3,4-tetrahydroisoquinoline, dissolved in 5 ml of dichloromethane, was nitrated as described above at ambient temperature using 65% nitric acid and a flow rate of 5  $\mu$ l/min. The work-up of the organic phase was carried out without prior neutralisation.

The same conditions were set for a continuous experiment, which was carried out continuously over six days. In this case, two syringes each with a capacity of 50 ml were used.

# 15 Example 2

A disposable plastic syringe having a capacity of 2 ml was filled with a 1:1 mixture consisting of toluene and dichloromethane. A second syringe was filled with 65% nitric acid. These two syringes were connected, and a flow rate of 5 µl/min was set. Under these conditions, the reaction was carried out at 0, 20 and 30°C.

The course of the reaction was monitored and recorded using a Merck Hitachi HPLC instrument (L 6200 pump, variable wavelength UV detector and D 2500 chromato integrator). The separating column used was a Merck Lichrocart<sup>®</sup> RP Select B 250/4.

Mixture of 70% of acetonitrile and 30% of water, mixed with 1% of trifluoroacetic acid

Flow rate: 0.6 ml/min

Solvent:

Detector wavelength: 215 nm.

The nitrations of toluene were monitored with the aid of a Hewlett-Packard 6890 series GC system with an HP 5973 mass selection detector.

- 12 -

In order to carry out the experiments with 100% nitric acid, one syringe was filled with nitric acid and the other with pure toluene. The nitrations were carried out at 0, 21, 40, 60 and 80°C.

In order to carry out the experiments with acetyl nitrate, one syringe was filled with a 1:1 mixture consisting of toluene and acetic anhydride and another was filled with 100% nitric acid. The contents of the two syringes were pumped simultaneously into two different inlet channels of a micromixer for intensive mixing and nitration. The nitrations were carried out at -10, 0, 21, 40 and 60°C, with the course of the reaction being monitored as described above.

15

20

25

30

10

15

20

30

- 13 -

#### PATENT CLAIMS

- 1. Process for the nitration of aromatic or heteroaromatic compounds, characterised in that the aromatic or heteroaromatic compound in liquid form or in solution is mixed intensively and allowed to react with a liquid or dissolved nitrating reagent, selected from the group consisting of dilute nitric acid, 100% nitric acid, potassium nitrate in 100% sulfuric acid, mixtures of nitric acid and sulfuric acid ("nitrating acid"), nitric acid esters, mixtures of nitric acid with inorganic and organic anhydrides and dinitrogen pentoxide, in a microreactor for an adequate residence time, and the desired nitration product is isolated from the resultant reaction mixture.
  - 2. Process according to Claim 1, characterised in that the microreactor used is a heatable flow reactor.
    - 3. Process according to Claims 1 and 2, characterised in that the process is continuous.
- Process according to Claims 1 to 3, characterised in that
   a) the aromatic or heteroaromatic compound is firstly derivatised,
  - b) the resultant derivative is dissolved in a solvent and
  - c) nitrated in a micromixer using a nitrating reagent, and
  - d) the nitrated product is isolated from the resultant solution.
- 5. Process according to one or more of Claims 1 to 4, characterised in that the nitrated product is separated off from the reaction mixture by extraction with a solvent.
  - 6. Process according to one or more of Claims 1 to 5, characterised in that the reaction mixture flows through the microreactor at an adequate flow rate of from 1 µl/min to 10 ml/min, and the reaction is carried out at a temperature in the range from -40 to 150°C, with the course of the reaction being monitored by gas chromatography.
- 7. Process according to Claim 6, characterised in that the reaction mixture flows through the microreactor at a flow rate of from 5 μl/min to 1 ml/min, and the reaction is carried out at a temperature in the range from -10 to

80°C, with the course of the reaction being monitored, if desired, continuously, by gas chromatography.

- 8. Process according to Claims 4 to 7, characterised in that an aromatic or heteroaromatic compound is converted into a carbamate in a first reaction step.
- 9. Process for the nitration of aromatic or heteroaromatic compounds selected from the group consisting of toluene, 1,2,3,4-tetrahydroiso-quinoline, N-methoxycarbonyl-1,2,3,4-tetrahydroisoquinoline and benzofuran derivatives according to one or more of Claims 1 to 8.

15

5

10

20

25

30

# **ABSTRACT**

The present invention relates to a novel process for the nitration of organic compounds, preferably of aromatic and heteroaromatic compounds, using nitrating reagents which are known from the literature and new types of nitrating reagents.

10

5

15

20

25


30

Figure 1

Influence of temperature on the nitration of toluene (100% HNO $_3$ 10  $\mu$ l/min)



5



25


30

2001



# Figure 2

# Influence of temperature on the nitration of toluene (acetyl nitrate, 20 $\mu$ l/min)



□0°C □21°C □40°C □60°C

25

30

As a below named inventor, I hereby declare that:  My residence, post office address and citizenship are as stated below next to my name.  I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled NITRATION IN A STATIC MICROMIXER  the specification of which (check only one item below):  is attached hereto.  was filed as United States application  Serial No. 10/048,157  on  and was amended  on (if applicable).  was filed as PCT international application  Number PCT/EP00/06317  on 05.07.2000,	
I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (iplural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled NITRATION IN A STATIC MICROMIXER  the specification of which (check only one item below):    is attached hereto.     was filed as United States application     Serial No. 10/048,157     on and was amended     on (if applicable).     was filed as PCT international application     Number PCT/EP00/06317	
plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled NITRATION IN A STATIC MICROMIXER  the specification of which (check only one item below):  is attached hereto.  was filed as United States application  Serial No. 10/048,157  on  and was amended  on (if applicable).  was filed as PCT international application  Number PCT/EP00/06317	
the specification of which (check only one item below):  is attached hereto.  was filed as United States application  Serial No. 10/048,157  on  and was amended  on (if applicable).  was filed as PCT international application  Number PCT/EP00/06317	,
is attached hereto.  was filed as United States application  Serial No. 10/048,157  on and was amended  on (if applicable).  was filed as PCT international application  Number PCT/EP00/06317	
was filed as United States application  Serial No. 10/048,157  on  and was amended  on (if applicable).  was filed as PCT international application  Number PCT/EP00/06317	
Serial No. 10/048,157  on and was amended  on (if applicable).  was filed as PCT international application  Number PCT/EP00/06317	,
and was amended  on (if applicable).  was filed as PCT international application  Number PCT/EP00/06317	
and was amended  on (if applicable).  was filed as PCT international application  Number PCT/EP00/06317	
on (if applicable).  was filed as PCT international application  Number PCT/EP00/06317	
was filed as PCT international application  Number PCT/EP00/06317	
Number <u>PCT/EP00/06317</u>	
on 05 07 2000	
011 05:07:2000,	
and was amended under PCT Article 19	
on (if applicable).	
I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, a amended by any amendment referred to above.	
I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.	
I hereby claim priority benefits under Title 35, United States Code, § 119 or 365 (b) of the following United States provisions application(s) and of any foreign application(s) for patent or inventor's certificate or 365(a) of any PCT internations application(s) designating at least one country other than the United States of America listed below and have also identifie below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by the on the same subject matter having a filing date before that of the application(s) of which priority is claimed:	<u>.</u>
PRIOR U.S. PROVISIONAL AND FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:	
COUNTRY (if PCT. indicate "PCT")  APPLICATION NUMBER  DATE OF FILING (day, month, year)  UNDER 35 USC	
Germany 199 35 692.0 07/29/99	NO
	NO NO
	<del>-</del>
YES .	OP
POWER OF ATTORNEY: As a named inventor, I hereby appoint I. William Millen (19,544); John L. White (17,746); Anthony J. Zelano (27,969); Alan E.J. Branigan (20,565); John R. Moses (24,983); Harry B. Shubin (32,004); Brion P. Heaney (32,542); Richard Traverso (30,595); John A. Sopp (33,103): Richard M. Lebovitz (37,067); James B. Ruland (37,432); Nancy Axelrod (44,014); Jenn J. Branigan (40,21); Robert E. McCarthy, (46,044); Jonathan G. Brown (47,451); and Csaba Henter (50,908) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.  Send Correspondence to: Customer No. 23599  Telephone No.  Direct Telephone Cal	40



, 23599 PATENT TRADEMARK OFFICE

Combined Declaration for Patent Application and Power of Attorney (Continued)
(Includes Reference to PCT International Applications)

ATTORNEY'S DOCKET NUMBER

$\overline{}$			FAMILY NAME	PIRST GIVEN NAME	SECOND GIVEN NAME
9		PULL NAME OF INVENTOR	FABIAN	Kai	
\	2		CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
`	0	RESIDENCE & CITIZENSHIP	69259 Wilhelmsfeld		German
	-		STREET	CITY	STATE & ZIP CODE/COUNTRY
		POST OFFICE ADDRESS	Oberer Langerain 13	ļ	Germany DEX
t	_	FULL NAME	PAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
$\supset$	2	OF INVENTOR	STOLDT	Joeran	
3/1	0	RESIDENCE &	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
/	2	CITIZENSHIP	64331 Weiterstadt		German
}		POST OFFICE	STREET	CITY	STATE & ZIP CODE/COUNTRY  Germany
L	L	ADDRESS	Kreuzstrasse 11		
1		FULL NAME	FAMILY NAME	FIRST GIVEN NAME Haddis	SECOND GIVEN NAME
ĺ	2	OF INVENTOR	WURZIGER		
	0	RESIDENCE &	СПУ	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
91	3	CITIZENSHIP	64291 Darmstadt		German
8		POST OFFICE	STREET	CITY	STATE & ZIP CODE/COUNTRY
		ADDRESS	Greinstrasse 7b		Germany DEX
		FULL NAME OF INVENTOR	PAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
j	2		SCHWESINGER	Norbert	
0	0	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
7	4		85386 Eching		German
$ \mathcal{X} $	-	POST OFFICE	STREET	CITY	STATE & ZIP CODE/COUNTRY
Ì		ADDRESS	Bahnstrasse 35		Germany DEX
ſ		FULL NAME	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
}	2	OF INVENTOR			
	0	RESIDENCE &	CITY	STATE OR FOLEIGN COUNTRY	COUNTRY OF CITIZENSHIP
	5	CITIZENSHIP			
		POST OFFICE	STREET	CITY	STATE & 2IP CODE/COUNTRY
		ADDRESS			
1		FULL NAME	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
1	2	OF INVENTOR			
1	0	RESIDENCE &	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
[	6	CITIZENSHIP	STREET	CITY	STATE & ZIP CODE/COUNTRY
}		POST OFFICE ADDRESS			STATE OF COUNTRY
ŀ			FAMILY NAME	PIRST GIVEN NAME	SECOND GIVEN NAME
1	_	PULL NAME OF INVENTOR			
- 1	2	RESIDENCE &	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
1	0 7	CITIZENSHIP			
1	′	POST OFFICE	STREET	CITY	STATE & ZIP CODE/COUNTRY
ł		ADDRÉSS			

Combined Declaration for Patent Application and Power of Attorney (Continued) (Includes Reference to PCT International Applications)	ATTORNEY'S DOCKET NUMBER
(Includes Assetted & 1 of International Approximation)	

2	FULL NAME OF INVENTOR	PAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
0 8	RESIDENCE & CITIZENSHIP	СПУ	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	POST OFFICE ADDRESS	STREET	CITY	STATE & ZIP CODE/COUNTRY
•	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
0	residence & Citizenship	CITY	STATE OF FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
9	POST OFFICE ADDRESS	STREET	כחץ	STATE & ZIP CODE/COUNTRY
	FULL NAME OF INVENTOR	FAMILY NAME	PIRST GIVEN NAME	SECOND GIVEN NAME
2	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
0	FOST OFFICE ADDRESS	STREET	CITY	STATE & ZIP CODE/COUNTRY
2 1 1	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	POST OFFICE ADDRESS	STREET	CITY	STATE & ZIP CODE/COUNTRY
2	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
1 2	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	POST OFFICE ADDRESS	STREET	CITY	STATE & ZIP CODE/COUNTRY

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

SIGNATURE OF INVENTOR 201	DATE 23.08.2002	SIGNATURE OF INVENTOR 207	DATE
SIGNATURE OF INVENTOR 202	DATE 23.08.2002	SIGNATURE OF INVENTOR 208	DATE
SIGNATURE OF INVENTOR 203	DATE 23.08.2002	SIGNATURE OF INVENTOR 209	DATE
SIGNATURE OF INVENTOR 204 Worberf Welling	DATE 23.08.2002	SIGNATURE OF INVENTOR 210	DATE
SIGNATURE OF INVENTOR 205	DATE	SIGNATURE OF INVENTOR 211	DATE
SIGNATURE OF INVENTOR 206	DATE	SIGNATURE OF INVENTOR 212	DATE